



Count on it.

DDC™ Series

Residential Controller

C O N T R O L L E R S

*The world is becoming digital...
why should your irrigation
controller be any different!*

*Introducing the DDC™ Series,
one of Toro's most exciting new
additions to its controller product
offering. Although compact in
size, several large features are
packed into the DDC –
making it extremely affordable
for any residential or light
irrigation application.*

*Available in 4, 6, or 8-station
models, the DDC features an
exclusive, patent-pending virtual
dial interface that guides a user
through simple programming
functions. Setting up an irrigation
schedule has never been easier!*

*The new DDC controller –
only from Toro.*



DDC Controller

4, 6 and 8 stations

Features

- Toro exclusive "digital dial" technology simulates the simplicity of a mechanical dial
- Large LCD display
- 3 independent programs, easily identified within "digital dial" interface
- 3 Start Times per Program
- 1 to 240 minute run times with delay between stations
- Multiple watering days options
 - 365 day calendar
 - 7 day calendar, 14 day interval
 - Odd/Even day watering, with 31st day exclusion
- 0 to 200% Seasonal Adjust or Water Budget setting in 10% increments
- Manual program start
- Semi-Auto feature to manually start programs stored in controller memory.
- Built-in Rain delay with sensor terminal hookups
- Self-diagnostic circuit breaker identifies irrigation faults
- "Arm Chair" programming with 9-volt battery power source
- Programmable Master Valve
- Convenient program review feature
- Display with multi-language overlays (user selectable)
- 5 Year program retention, with on board coin battery
- Default program if loss of power occurs
- Large terminal screws for easy installation and wiring
- Quick reference card for programming assistance
- CE, EMC, C-tick, FCC and ETL approved
- 2 year warranty

Electrical Specifications

Input power:

- 120 VAC, 50/60 Hz (Plug-in transformer, UL/CUL approved)
- 230 VAC, 50/60 Hz (Plug-in transformer, CE Mark)
- 240 VAC, 50/60 Hz (Plug-in transformer, SAA)
- 60 W (0.50 amps) maximum

Station Output Power:

- 24 VAC
 - 6 VA (0.25 amps) per station maximum
 - 6 VA (0.25 amps) pump start/master valve
 - 12 VA (0.50 amps) total load

Mechanical Specifications

Indoor:

- Weight without 9-volt battery: 280 grams (9 ounces)
- Dimensions: 127,5 x 145 x 400mm (H x W x D)
5" x 5³/₄" x 11¹/₂"D (H x W x D)
- 500mA class 2 transformer

Outdoor**:

- Weight without 9-volt battery: 1,14 kilos (2.5 lbs.)
- Dimensions: 178 x 89 x 220 mm (H x W x D)
8 ⁵/₈" x 3 ¹/₂" x 7" (H x W x D)

** Contact your local Toro distributor for availability.

Specifying Information

DDC X XXX OD			
Description	Stations	Voltage	Optional
DDC - Digital Dial Controller	4 - 4 station 6 - 6 station 8 - 8 station	120 - 120 V a.c. 220 - 220 V a.c. 240 - 240 V a.c.	OD - outdoor cabinet*
For Example: When specifying an 8 station DDC controller with 220 V a.c. plug-in transformer, you would specify: DDC-8-220			

* Contact your local Toro distributor for availability.



Count on it.

Worldwide Headquarters
 The Toro Company
 8111 Lyndale Avenue South
 Bloomington, MN 55420
 Phone: 952-888-8801
 Fax: 952-887-7265
www.toro.com

GB Form Number: 200-2218
 ©2005 The TORO COMPANY – All Rights Reserved.